



ANTI UV WOODSTAIN

- *Absolute protection from ultraviolet radiation*
- *High concentration in anti UV agents*
- *Preserves the natural aspect of the wood*



DESTINATION

- Shutters - Doors - Windows - Paneling

PROPERTIES

Colorless Anti-UV woodstain: formula rich in anti-UV agents, that guarantees effective

long-lasting protection against extreme climatic conditions. Does not flake.

PREPARATION

- Bare woods: Lightly sand the bare wood and remove dust. For maximum protection, use an exterior wood treatment first.
- Already stained woods: Remove existing loose flaking coating using a stiff brush, proceed to a light sanding with fine abrasive paper to obtain a smooth surface and remove dust.
- Exotic woods: direct application except Iroko or Wengé, for them first apply the appropriate V33 undercoat.

HOW TO APPLY

Ideal application conditions: between 12 and 25°C in dry weather and without draft.

- Stir well the stain before and during use with a long and large stick .
- Apply 2 coats using a brush or a spray gun on a clean, dry and degreased wood.
- Between coats: proceed to a slight sanding with fine abrasive paper to obtain a smooth surface and remove dust.

PROTECTION

The 6 year duration concerns:

- new or to renovate woods from common species: in accordance with the method of preparation and application.
- on vertical woodwork only. South and South-West exposure: apply 3 layers.

The guarantee is limited to reimbursement of the product (on presentation of the bottle and the receipt) and covers only the appearance of the woodstain.

The 6 years duration depends on the exposure and on the weather conditions. This period may be reduced in the event of severe weather conditions or of surfaces in constant exposure with moisture when the water can not run.

Αδιάβροχο



Aspect : satin

Sizes : 0.75L, 2.5L

Drying time :

Between coats : 12h

Total : 24h

Coverage in 1 coat, per L: 12m²

Cleaning : White spirit

Tools : brush, roller & spray gun



SAFETY RECOMMENDATIONS and PRECAUTIONS FOR USE



WARNING

EUH208: Contains 2-butanone oxime. May produce an allergic reaction. H226: Flammable liquid and vapour. EUH066: Repeated exposure may cause skin dryness or cracking. P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Close the container after use. EU limit value for this product (Category A/e - Interior/exterior trim varnishes and woodstains, including opaque woodstains): 400g/l (2010). This product contains max 400g/l VOC.