



ΒΕΡΝΙΚΙ ΠΕΤΡΑΣ

STONE VARNISH



- Αδιάβροχο
- Αντιολισθητικό



ΜΑΚΡΟΧΡΟΝΙΑ ΠΡΟΣΤΑΣΙΑ



CHARACTERISTICS

V33 STONE VARNISH is a colourless, waterproof varnish for use on all floors and walls made from natural or artificial stone. It penetrates the stone making it stronger and enables it to keep its natural colour.

V33 STONE VARNISH will protect the stone from water and general weathering. On floors and walls it provides protection against heavy use or knocks.

It does not peel-off, it is non-slippery and is suitable for inside and outside use.

DESTINATION

- V33 STONE VARNISH can be used on all natural and artificial stone and on marble, brick, ceramics and concrete.

It's also suitable for Karystos stones.

SHADE

CLEAR
SATIN

APPLICATION

The surface to be covered with V33 STONE VARNISH should be clean, dry and porous. V33 STONE VARNISH can be applied in one thick coat using a clean and soft paintbrush. Very absorbent surfaces may require two coats.

How can you check if the support is porous : let water drop on the support to be varnished. If the water remains at the surface, the support is not porous and the varnish will not stick on it.

In order to obtain a good adhesion of the varnish, apply on the support with a brush or a watering can a mixed solution made of 20% of hydrochloric acid and 80% of water (1 liter for about 5m²).

Wear suitable protective clothing and wear eye protection. Let it dry for 48 hours, rinse out with water and remove dust..



WARNING

EUH208: Contains ethylmethylketoxime. May produce an allergic reaction. H226: Flammable liquid and vapour. EUH066: Repeated exposure may cause skin dryness or cracking. P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). EU limit value for this product (cat. A/e): 400g/l (2010). This product contains max 400g/l VOC. Help to protect the environment - do not empty unused product into drains. Close the container after use.