



ΒΕΡΝΙΚΙ ΘΑΛΑΣΣΗΣ BOAT VARNISH

- **Water repellent**
- **High resistance to coastal climates and solar radiation.**



DESTINATION

- Suitable for all types of European and exotic wood.
- Recommended for exterior woodwork subject to difficult exposure: boat bridges, gateways, seaside house doors and windows, terraces, balconies...

CHARACTERISTICS

- This Marine Varnish, based on polyurethane resins and anti-UV gives optimal protection to your outdoor window and door frames, subject to marine climates and heavy exposure to the sun.
- Its formulation makes it absolutely waterproof and resistant to sea salts.
- Its strong abrasion-resistance means it can be applied in outdoor passage ways: terraces, balconies, outdoor stairways.

SHADE

CLEAR
GLOSS

SURFACE PREPARATION

- BARE WOOD: Brush and remove dust.
- VARNISHED WOOD: Carefully sand using fine glass-paper (240). If the varnish has scaled, strip it using V33 Universal Stripper. Rinse with water.

Let dry for 24 h.

APPLICATION

- Stir well before use.
- Apply with a flat brush or spray gun in two coats on clean, dry and completely degreased wood. Let the first coat dry for 6 hours. Sand lightly with fine glass paper (240) and dust before applying the second coat

TIPS FOR APPLICATION

- Ideal conditions for application: 12°C to 25°C in dry weather.
- You are recommended to degrease oily wood before applying the varnish. You are recommended to slightly round the corners of your woodwork with glass-paper, to ensure an even coat of varnish.



WARNING

Contains Naphtha (petroleum), hydrotreated heavy.

EUH208: Contains ethylmethylketoxime. May produce an allergic reaction. H226: Flammable liquid and vapour. H336: May cause drowsiness or dizziness. EUH066: Repeated exposure may cause skin dryness or cracking. P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority).
EU limit value for this product (cat. A/e): 400g/l (2010). This product contains max 400g/l VOC.