



UNIVERSAL WOODSTAIN

- *High resistance to UV and weather conditions*
- *Quick drying*



DESTINATION

- Ideal for portals, windows, panelling, shutters, beams.
- Compatible with European woods except Iroko and exotic woods..

PROPERTIES

- Ready-to-use product. Impregnates, decorates and protects the wood.
- Enhances wood grain. Do not flake off.
- High protection against UV rays and bad weather conditions.
- Waterproof: protects wood against rain and humidity.
- Microporous: let wood breathe while avoiding water to penetrate.
- Compatible with all old solvent based wood stain

PREPARATION

Ensure wood is clean, dry and free from dust.

- Bare woods: Lightly sand the bare wood and remove dust. For maximum protect use V33 Multi Use Treatment for Wood first.
- Already stained woods: Remove existing loose flaking coating using a stiff brush, proceed to a light sanding with fine abrasive paper to obtain a smooth surface and remove dust.

HOW TO APPLY

The colour in the tin does not correspond with the final colour/shade. Milky consistency in the tin that disappears after application.

- Shake/stir well before use with the help of a stick.
- Apply 2 coats using a brush or a roller
- Between coats: proceed to a slight sanding with fine abrasive paper to obtain a smooth surface and remove dust.
- Ideal application conditions: between 12 and 25° C on a not too warm wood in order to avoid spots appearing when drying.

IMPORTANT

- On new or heavy exposed wood, it is recommended to apply a third coat as when using the lighter shades. The clear shade is recommended for interior use only. For an exterior use, the clear may be used to dilute the tones other shades.
- The obtained shade depends on the initial colour of the wood and of its age. The older the wood is, the darker the result. Rub down the surface lightly with fine abrasive paper between coats in order to obtain a smooth surface.



Aspect: satin
Sizes: 0.75L, 2.5L
DRYING TIME
 3H between coats
 12H complete drying time
Coverage in 1 coat, per L: 12m²
Cleaning: Water
Tools: brush, roller, spray gun



SAFETY RECOMMENDATIONS and PRECAUTIONS FOR USE

EUH208: Contains 1,2-benzisothiazol-3(2H)-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H -isothiazol-3-one (3:1). May produce an allergic reaction. P102: Keep out of reach of children. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Do not allow to freeze. Close the container after use. EU limit value for this product (Category A/e - Interior/exterior trim varnishes and woodstains, including opaque woodstains): 130g/l (2010). This product contains max 47g/L VOC.