



CLASSIC WOODSTAIN

- *Absolute protection from ultraviolet radiation*
- *High concentration in anti UV agents*
- *Preserves the natural aspect of the wood*



DESTINATION

For all exterior vertical woodwork: shutters, gates, fences, windows, beams, cladding, garden houses ...

- On all types of new and old European and exotic woods
- Compatible with all types of previously applied woodstains

PROPERTIES

- Water repellent microporous formulation: lets the wood breathe by blocking water and moisture.
- Easy application.

PREPARATION

The wood to be stained must be clean and dry.

- RAW WOOD: sand with sandpaper to obtain a smooth surface and remove dust. Pre-treat your wood with the V33 exterior treatment
- ALREADY STAINED WOODS: brush to remove non-adhering parts. Sand with sandpaper to obtain a smooth surface and remove dust.
- EXOTIC, BLACK WOODS, OAK: apply first a suitable undercoat
- GREASY WOODS : degrease.

HOW TO APPLY

Ideal application conditions: between 12 and 25°C in dry weather and without draft.

Milky appearance in the tin that disappears after drying.

- Stir well the stain before and during use with a long and large stick .
- Apply with 2 coats with a brush, a spray gun or a roller.

PROTECTION

The 5 year duration concerns:

- new or to renovate woods from common species: in accordance with the method of preparation and application.
- on vertical woodwork only. South and South-West exposure: apply 3 layers.

The guarantee is limited to reimbursement of the product (on presentation of the bottle and the receipt) and covers only the appearance of the woodstain.

The 5 years duration depends on the exposure and on the weather conditions. This period may be reduced in the event of severe weather conditions or of surfaces in constant exposure with moisture when the water can not run.



Special exterior

Aspect : satin

Sizes : 0.75L, 2.5L,

Drying time :
Between coats : 6h
Total : 12h

Coverage in 1 coat, per L: 12m²

Cleaning : White spirit

Tools : brush, roller & spray gun



SAFETY RECOMMENDATIONS and PRECAUTIONS FOR USE



WARNING

EUH208: Contains tallol fatty acids, fatty acids C18 insaturated trimers and 2-butanone oxime. May produce an allergic reaction. H226: Flammable liquid and vapour. EUH066: Repeated exposure may cause skin dryness or cracking. P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flflames and other ignition sources. No smoking. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority). Close the container after use. EU limit value for this product (Category A/e - Interior/exterior trim varnishes and woodstains, including opaque woodstains): 400g/l (2010).This product contains max 400g/l VOC.